

LEITZ PRIMES

TECHNICAL SPECIFICATIONS

Focal Length (mm)	18	21	25	29	35	40	50	65	75	100	135	180
Aperture	T 1.8											T 2
Image Circle	46.5 mm											
Close Focus (ft)	1'10"	1'10"	1'10"	1'2"	1'6"	1'2"	1'7"	2'2"	2'6"	3'11"	3'11"	4'11"
Close Focus (m)	0.55	0.55	0.55	0.35	0.45	0.35	0.47	0.65	0.75	1.2	1.2	1.5
Horizontal angle of view "Full Frame" 36 x 24 mm	90.0°	81.2°	71.5°	63.7°	54.4°	48.5°	39.6	31.0°	27.0°	20.4°	15.2°	11.4°
Horizontal angle of view "Super 35" 24.9 x 18.7 mm	69.3°	61.3°	52.9°	46.5°	39.1°	34.6°	28.0°	21.7°	18.8°	14.2°	10.5°	7.9°
Weight (lb)	7.1	6.1	6.2	5.9	6.3	6.0	6.0	6.1	6.2	6.1	6.4	6.8
Weight (kg)	3.2	2.76	2.8	2.67	2.87	2.71	2.7	2.78	2.83	2.77	2.89	3.1
Length (in / mm)	7.9 / 201.5	7.2 / 183.7										7.9 / 201.5



Lens Mount	PL, LPL with Cooke/i metadata interface
Front Diameter	114 mm
Front Filter	M 112 x 1.5 mm screw-in
Rear Filter	Via net holder
Matched Focus/Iris Ring Locations	All focal lengths
Focus Rotation	270° (except 18 mm 207°)
Iris Rotation	66° (except 18 mm 63°)
Focus scales	Turnable scale, easy change from imperial to metric
Iris Blades	15
Iris Shape	Circular through all stops

